

1

FOUNDATION FOR INTELLIGENT PHYSICAL AGENTS

2

3

4

5

FIPA ACL Message Representation in 6 Bit-Efficient Encoding Specification

7

Document title	FIPA ACL Message Representation in Bit-Efficient Encoding Specification		
Document number	SC00069G	Document source	FIPA TC Agent Management
Document status	Standard	Date of this status	2002/12/03
Supersedes	FIPA00024		
Contact	fab@fipa.org		
Change history	See <i>Informative Annex A — ChangeLog</i>		

8

9

10

11

12

13

14

15

16

17

18 © 1996-2002 Foundation for Intelligent Physical Agents
19 <http://www.fipa.org/>
20 Geneva, Switzerland

Notice

Use of the technologies described in this specification may infringe patents, copyrights or other intellectual property rights of FIPA Members and non-members. Nothing in this specification should be construed as granting permission to use any of the technologies described. Anyone planning to make use of technology covered by the intellectual property rights of others should first obtain permission from the holder(s) of the rights. FIPA strongly encourages anyone implementing any part of this specification to determine first whether part(s) sought to be implemented are covered by the intellectual property of others, and, if so, to obtain appropriate licenses or other permission from the holder(s) of such intellectual property prior to implementation. This specification is subject to change without notice. Neither FIPA nor any of its Members accept any responsibility whatsoever for damages or liability, direct or consequential, which may result from the use of this specification.

21 **Foreword**

22 The Foundation for Intelligent Physical Agents (FIPA) is an international organization that is dedicated to promoting the
23 industry of intelligent agents by openly developing specifications supporting interoperability among agents and agent-
24 based applications. This occurs through open collaboration among its member organizations, which are companies and
25 universities that are active in the field of agents. FIPA makes the results of its activities available to all interested parties
26 and intends to contribute its results to the appropriate formal standards bodies where appropriate.

27 The members of FIPA are individually and collectively committed to open competition in the development of agent-
28 based applications, services and equipment. Membership in FIPA is open to any corporation and individual firm,
29 partnership, governmental body or international organization without restriction. In particular, members are not bound to
30 implement or use specific agent-based standards, recommendations and FIPA specifications by virtue of their
31 participation in FIPA.

32 The FIPA specifications are developed through direct involvement of the FIPA membership. The status of a
33 specification can be either Preliminary, Experimental, Standard, Deprecated or Obsolete. More detail about the process
34 of specification may be found in the FIPA Document Policy [f-out-00000] and the FIPA Specifications Policy [f-out-
35 00003]. A complete overview of the FIPA specifications and their current status may be found on the FIPA Web site.

36 FIPA is a non-profit association registered in Geneva, Switzerland. As of June 2002, the 56 members of FIPA
37 represented many countries worldwide. Further information about FIPA as an organization, membership information,
38 FIPA specifications and upcoming meetings may be found on the FIPA Web site at <http://www.fipa.org/>.

39 **Contents**

40	1 Scope.....	1
41	2 Bit-Efficient ACL Representation	2
42	2.1 Component Name	2
43	2.2 Syntax.....	2
44	2.3 Using Dynamic Code Tables.....	5
45	2.4 Notes on the Grammar Rules.....	7
46	3 References	9
47	4 Informative Annex A — ChangeLog	10
48	4.1 2002/11/01 - version F by TC X2S	10
49	4.2 2002/12/03 - version G by FIPA Architecture Board	10

50 **1 Scope**

51 This document deals with message transportation between inter-operating agents and also forms part of the FIPA
52 Agent Management Specification [FIPA00023]. It contains specifications for:

- 53 • Syntactic representation of ACL in a bit-efficient form.

55

56 2 Bit-Efficient ACL Representation

57 This section defines the message transport syntax for a bit-efficient encoding which is expressed in standard EBNF
 58 format¹ (see *Table 1*).

59

Grammar rule component	Example
Terminal tokens are enclosed in double quotes	" ("
Non-terminals are written as capitalised identifiers	Expression
Square brackets denote an optional construct	[" , " OptionalArg]
Vertical bars denote an alternative between choices	Integer Float
Asterisk denotes zero or more repetitions of the preceding expression	Digit*
Plus denotes one or more repetitions of the preceding expression	Alpha+
Parentheses are used to group expansions	(A B)*
Productions are written with the non-terminal name on the left-hand side, expansion on the right-hand side and terminated by a full stop	ANonTerminal = "terminal".
0x?? is a hexadecimal byte	0x00

60

61 **Table 1:** EBNF Rules

62

63 2.1 Component Name

64 The name assigned to this component is:

65

66 fipa.acl.rep.bitefficient.std

67

68 2.2 Syntax

```

69    ACLCommunicativeAct      = Message.
70
71    Message                  = Header MessageType MessageParameter* EndofMsg .
72
73    Header                   = MessageId Version.
74
75    MessageId                = 0xFA
76                               | 0xFB
77                               | 0xFC.                                /* See comment 1 below */
78
79    Version                  = Byte.                                /* See comment 2 below */
80
81    EndofMsg                 = EndOfCollection.
82
83    EndOfCollection          = 0x01.
84
85    MessageType               = PredefinedMsgType
86                               | UserDefinedMsgType.           /* See comment 3 below */
87
88    UserDefinedMsgType       = 0x00 MsgTypeName.
89
90    MsgTypeName               = BinWord.
91
92    MessageParameter          = PredefinedParam
93                               | UserDefinedMsgParam.         /* See comment 4 below */
94
95    UserDefinedMsgParam      = 0x00 ParameterName ParameterValue.
96
97    ParameterName             = BinWord.
```

¹ White space is not allowed between tokens.

```

98
99 ParamterValue      = BinExpression.
100
101 PredefinedMsgType = 0x01          /* accept-proposal */
102           | 0x02          /* agree */
103           | 0x03          /* cancel */
104           | 0x04          /* cfp */
105           | 0x05          /* confirm */
106           | 0x06          /* disconfirm */
107           | 0x07          /* failure */
108           | 0x08          /* inform */
109           | 0x09          /* inform-if */
110           | 0x0a          /* inform-ref */
111           | 0x0b          /* not-understood */
112           | 0x0c          /* propagate */
113           | 0x0d          /* propose */
114           | 0x0e          /* proxy */
115           | 0x0f          /* query-if */
116           | 0x10          /* query-ref */
117           | 0x11          /* refuse */
118           | 0x12          /* reject-proposal */
119           | 0x13          /* request */
120           | 0x14          /* request-when */
121           | 0x15          /* request-whenever */
122           | 0x16.         /* subscribe */
123
124 PredefinedMsgParam = 0x02 AgentIdentifier /* sender */
125           | 0x03 RecipientExpr   /* receiver */
126           | 0x04 MsgContent     /* content */
127           | 0x05 ReplyWithParam /* reply-with */
128           | 0x06 ReplyByParam   /* reply-by */
129           | 0x07 InReplyToParam /* in-reply-to */
130           | 0x08 ReplyToParam   /* reply-to */
131           | 0x09 Language        /* language */
132           | 0x0a Encoding        /* encoding */
133           | 0x0b Ontology        /* ontology */
134           | 0x0c Protocol        /* protocol */
135           | 0x0d ConversationID./* conversation-id */
136
137 AgentIdentifier    = 0x02 AgentName
138           [Addresses]
139           [Resolvers]
140           (UserDefinedParameter)*
141           EndOfCollection.
142
143 AgentName          = BinWord.
144
145 Addresses          = 0x02 UrlCollection.
146
147 Resolvers          = 0x03 AgentIdentifierCollection.
148
149 UserDefinedParameter = 0x04 BinWord BinExpression.
150
151 UrlCollection      = (Url)* EndofCollection.
152
153 Url                = BinWord.
154
155 AgentIdentifierCollection = (AgentIdentifier)* EndOfCollection.
156
157 RecipientExpr       = AgentIdentifierCollection.
158
159 MsgContent          = BinString.
160
161

```

```

162 ReplyWithParam          = BinExpression.
163
164 ReplyByParam            = BinDateTimeToken.
165
166 InReplyToParam          = BinExpression.
167
168 ReplyToParam             = RecipientExpr.
169
170 Language                = BinExpression.
171
172 Encoding                = BinExpression.
173
174 Ontology                = BinExpression.
175
176 Protocol                = BinWord.
177
178 ConversationID          = BinExpression.
179
180 BinWord                 = 0x10 Word 0x00
181 | 0x11 Index.
182
183 BinNumber               = 0x12 Digits           /* Decimal number */
184 | 0x13 Digits.           /* Hexadecimal number */
185
186 Digits                  = CodedNumber+.
187
188 BinString                = 0x14 String 0x00      /* New string literal */
189 | 0x15 Index.            /* String literal from code table */
190 | 0x16 Len8 ByteSeq.     /* New ByteLengthEncoded string */
191 | 0x17 Len16 ByteSeq.    /* New ByteLengthEncoded string */
192 | 0x18 Index.            /* ByteLengthEncoded from code table */
193 | 0x19 Len32 ByteSeq.    /* New ByteLengthEncoded string */
194
195 BinDateTimeToken          = 0x20 BinDate           /* Absolute time */
196 | 0x21 BinDate.          /* Relative time (+) */
197 | 0x22 BinDate.          /* Relative time (-) */
198 | 0x24 BinDate TypeDesignator /* Absolute time */
199 | 0x25 BinDate TypeDesignator /* Relative time (+) */
200 | 0x26 BinDate TypeDesignator. /* Relative time (-) */
201
202 BinDate                  = Year Month Day Hour Minute Second Millisecond.
203                                         /* See comment 8 below */
204
205 BinExpression             = BinExpr
206 | 0xFF BinString.        /* See comment 9 below */
207
208 BinExpr                  = BinWord
209 | BinString
210 | BinNumber
211 | ExprStart BinExpr* ExprEnd.
212
213 ExprStart                = i 0x60           /* Level down (i.e. '(' -character)
214 | 0x70 Word 0x00          /* Level down, new word follows */
215 | 0x71 Index.             /* Level down, word code follows */
216 | 0x72 Digits.            /* Level down, number follows */
217 | 0x73 Digits.            /* Level down, hex number follows */
218 | 0x74 String 0x00         /* Level down, new string follows */
219 | 0x75 Index.              /* Level down, string code follows */
220 | 0x76 Len8 String.       /* Level down, new byte string (1 byte) */
221 | 0x77 Len16 String.      /* Level down, new byte string (2 byte) */
222 | 0x78 Len32 String.      /* Level down, new byte string (4 byte) */
223 | 0x79 Index.              /* Level down, byte string code follows */
224
225 ExprEnd                  = 0x40           /* Level up (i.e. ')' -character)

```

```

226          | 0x50 Word 0x00    /* Level up, new word follows      */
227          | 0x51 Index       /* Level up, word code follows    */
228          | 0x52 Digits      /* Level up, number follows      */
229          | 0x53 Digits      /* Level up, hexadecimal number follows */
230          | 0x54 String 0x00 /* Level up, new string follows   */
231          | 0x55 Index       /* Level up, string code follows */
232          | 0x56 Len8 String /* Level up, new byte string (1 byte) */
233          | 0x57 Len16 String/* Level up, new byte string (2 byte) */
234          | 0x58 Len32 String/* Level up, new byte string (4 byte) */
235          | 0x59 Index.      /* Level up, byte string code follows */

236
237 ByteSeq        = Byte*.

238
239 Index          = Byte
240             | Short.           /* See comment 6 below */

241
242 Len8           = Byte.           /* See comment 7 below */

243
244 Len16          = Short.          /* See comment 7 below */

245
246 Len32          = Long.           /* See comment 7 below */

247
248 Year            = Byte Byte.

249
250 Month          = Byte.

251
252 Day             = Byte.

253
254 Hour            = Byte.

255
256 Minute          = Byte.

257
258 Second          = Byte.

259
260 Millisecond     = Byte Byte.

261
262 Word             = /* as in [FIPA00070] */

263
264 String           = /* as in [FIPA00070] */

265
266 CodedNumber      = /* See comment 5 below */

267
268 TypeDesignator   = /* as in [FIPA00070] */

269

```

2.3 Using Dynamic Code Tables

The transport syntax can be used with or without dynamic code table. Using dynamic code tables is an optional feature, which gives more compact output but might not be appropriate if communicating peers does not have sufficient memory (for example, in case of low-end PDAs or smart phones).

To use dynamic code tables the encoder inserts new entries (for example, Word, String, etc.) into a code table while constructing bit-efficient representation for ACL message. The code table is initially empty and whenever a new entry is added to the code table, the smallest available code number is allocated to it. There is no need to transfer these index codes explicitly over the communication channel. Once the code table becomes full and a new code needs to be added, the sender first removes $\text{size} >> 3^2$ ² entries from the code table using a Least Recently Used (LRU) algorithm and then adds a new entry to code table. For example, should the code table size be 512 entries, 64 entries are removed. Correspondingly the decoder removes entries from the code table when it receives a new entry from the encoder.

² Right shifted by 3 bit positions – approximately 10%.

283 The size of the code table, if used, is between 256 (2^8) and 65536 (2^{16}) entries. The output of this code table is always
284 one or two bytes (one byte only when the code table size is 2^8). Using two-byte output code wastes some bits, but
285 allows for much faster parsing of messages. The code table is unidirectional, that is, if sender A adds something to the
286 code table when sending a message to B, then B cannot use this code table entry when sending a message back to A.
287

288 Both peers must agree the code table size before its usage; this process is not part of this specification. Furthermore,
289 having more compact output, one code table should be applied to more than one message; the method of mapping
290 messages to appropriate code table is not part of this specification.
291

292 2.4 Notes on the Grammar Rules

- 293 1. The first byte defines the message identifier. The identifier byte can be used to separate bit-efficient ACL messages
 294 from (for example) string-based messages and separate different coding schemes. The value 0xFA defines a bit-
 295 efficient coding scheme without dynamic code tables and the value 0xFB defines a bit-efficient coding scheme with
 296 dynamic code tables. The message identifier 0xFC is used when dynamic code tables are being used, but the
 297 sender does not want to update code tables (even if message contains strings that should be added to code table).
 298
- 299 2. The second byte defines the version number. The version number byte contains the major version number in the
 300 upper four bits and minor version number in the lower four bits. This specification defines version 1.0 (coded as
 301 0x10).
- 302 3. All message types defined in this specification have a predefined code. If an encoder sends an ACL message with
 303 a message type which has no predefined code, it must use the extension mechanism which adds a new message
 304 type into code table (if code tables are being used).
- 305 4. All message parameters defined in this specification have a predefined code. If a message contains a user defined
 306 message parameter, an extension mechanism is used (byte 0x00) and new entry is added to code table (if code
 307 table is used).
- 308 5. Numbers are coded by reserving four bits for each digit in the number's ASCII representation, that is, two ASCII
 309 numbers are coded into one byte. *Table 1* shows a 4-bit code for each number and special codes that may appear
 310 in ASCII coded numbers.

311 If the ASCII presentation of a number contains odd number characters, the last four bits of the coded number are
 312 set to zero (the Padding token), otherwise an additional 0x00 byte is added to end of coded number. If the
 313 number to be coded is integer, decimal number, or octal number, the identifier byte 0x12 is used. For hexadecimal
 314 numbers, the identifier byte 0x13 is used. Hexadecimal numbers are converted to integers before coding (the
 315 coding scheme does not allow characters from a through f to appear in number form).

316 Numbers are never added to a dynamic code table.

Token	Code	Token	Code
Padding	0000	7	1000
0	0001	8	1001
1	0010	9	1010
2	0011	+	1100
3	0100	E	1101
4	0101	-	1110
5	0110	.	1111
6	0111		

323 324 **Table 1:** Binary Representation of Number Tokens

- 325 6. Index is a pointer to code table entry and its size (in bits) depends on the code table size. If the code table size is
 326 256 entries, the size of the index is one byte; otherwise its size is two bytes (represented in network byte order).
 327
- 328 7. Byte is a one-byte code word, Short is a short integer (two bytes, network byte order) and Long is a long integer
 329 (four bytes, network byte order).
 330

- 332 8. Dates are coded as numbers, that is, four bits are reserved for each ASCII number (see comment 5 above).
333 Information whether the type designator is present or not, is coded into identifier byte. These fields always have
334 static length (two bytes for year and milliseconds, one byte for other components).
335
336 9. None of the actual content of the message (the information contained in the content parameter of the ACL
337 message) is coded nor are any of its components are added to a code table.
338

339 3 References

- 340 [FIPA00023] FIPA Agent Management Specification. Foundation for Intelligent Physical Agents, 2000.
341 <http://www.fipa.org/specs/fipa00023/>
- 342 [FIPA00067] FIPA Agent Message Transport Service Specification. Foundation for Intelligent Physical Agents, 2000.
343 <http://www.fipa.org/specs/fipa00067/>
- 344 [FIPA00070] FIPA ACL Message Representation in String Specification. Foundation for Intelligent Physical Agents, 2000.
345 <http://www.fipa.org/specs/fipa00070/>
- 346 [FIPA00075] FIPA Agent Message Transport Protocol for IIOP Specification. Foundation for Intelligent Physical Agents, 2000.
347 <http://www.fipa.org/specs/fipa00075/>
- 348
349
350

351 4 Informative Annex A — ChangeLog

352 4.1 2002/11/01 - version F by TC X2S

353 Page 2, line 56: Removed sentence on compatibility issue with FIPA00075
354 **Page 4, line 158:** **MsgContent value changed from BinExpression to BinString**
355 **Page 4, line 193:** **Added signs to BinDateTimeToken**

356 357 4.2 2002/12/03 - version G by FIPA Architecture Board

358 Entire document: Promoted to Standard status
359